

WHAT ARE THE DIFFERENCES?

BETWEEN THE MEMPAC™-M AND THE MEMPAC™-E

STANDARD FEATURES

	MEMPAC™-M	MEMPAC™-E
All bases, skids and supports are fabricated from 304 stainless steel	☐	☐
304 stainless steel tankage	☐	
304 stainless steel reactor tankage		☐
Stainless steel controls panels	☐	
Powder coated controls panels		☐
Cutting-edge controls system	☐	☐
Human Machine Interface (HMI)	☐	☐
All sensory equipment is mounted on Cloacina's patented Slide Rail™ System	☐	☐
Influent screening	☐	☐
Above-ground installation	☐	☐
All piping, valves and fittings will be a minimum of Schedule 80 PVC	☐	☐
Automated Clean In Place (CIP) system	☐	☐
Submerged membrane cassette(s)	☐	☐
Modular, medium fine bubble diffusers	☐	☐
Semi-sound attenuated aeration equipment	☐	
Full length catwalk	☐	

OPTIONAL FEATURES FOR BOTH MODELS

- Nutrient removal
- Buried installation
- pH adjustment system
- Disinfection
- Package lift station
- Prefabricated controls building
- Sludge disposal equipment
- Incorporation of existing equipment into Cloacina's controls system
- Energy saving controls system upgrades
- Equalization
- Additional equipment sound attenuation
- Thermal protection
- Mobile units
- Odor mitigation equipment
- Automated foam control
- Sediment/grit traps
- A variety of grating, covers and awnings are available
- Project management and equipment installation



CLOACINA.COM
888.483.8469