

## Cerabar M PMC51

Pressure, capacitive.  
compact.  
Application: pressure/level.  
Membrane: Ceraphire,  
dry, vacuum proof.  
:: Easiest on-site operation.  
:: Modular.

**PMC51-AA21JD1HGFRKJA**

**71086208**

SPK: PAB



### Basic model

Cerabar M PMC51

### Approval:

AA Non-hazardous area

### Output:

2 4-20mA HART

### Display, Operation:

1 LCD, push button on display/electronics

### Housing:

J F31 Alu, glass window

### Electrical Connection:

D Thread NPT1/2, IP66/68 NEMA4X/6P

### Sensor Range:

1H 1bar/100kPa/15psi gauge, 10mH2O/33ftH2O/400inH2O overload: 10bar/1MPa/150psi

### Reference Accuracy:

G Standard

### Calibration; Unit:

F Sensor range; psi

### Process Connection:

RKJ Thread ANSI MNPT1/2 hole 11.4mm, 316L

### Seal:

A FKM Viton

### >Additional Operation Language:

### >Calibration:

### >>Service:

### >>Test, Certificate:

### >>Additional Approval:

### >Separate Housing:

### >>Accessory Mounted:

### >>Accessory Enclosed:

### >Firmware Version:

### >>Marking:

### Total price